AV02 RV 1500



Premium commercial vertical air handling units with a rotary heat exchanger

- Sound pressure level LpA at 3 m: 35
- Heat exchanger type: Rotary, condensation or enthalpy
- Heat exchanger material: Aluminium/aluminium with hygroscopic coating
- Supply filter: ePM1 70% (ISO 16890)-F7 (EN779)
- Extract filter: ePM1 70% (ISO 16890)-F7 (EN779)
- Sound-insulated casing
- Reheater: Optional
- Preheater: Optional
- BMS protocol: ModBus, Bacnet
- Casing material: Aluzinc steel

	Unit of measurement	AV02 RV 1500
Casing performance	-	40 mm, T3/TB4
Connected air duct size	mm	500x250
Phases	-	1
Maximum supply voltage	V	240
Minimum supply voltage	V	200
Power supply frequency	Hz	50/60
Rated power supply fan	W	700
Rated power extract fan	W	700
Unit current (without electric heaters)	A	6.5
Maximum airflow	m³/h	1950
Maximum airflow at ESP 200 Pa	m³/h	1800
Sound pressure level LpA at 3 m	dB(A)	35
Heat exchanger type	-	Rotary, condensation or enthalpy
Heat exchanger material	-	Aluminium/aluminium with hygroscopic coating
Weight	kg	295
Supply filter	-	ePM1 70% (ISO 16890)-F7 (EN779)
Extract filter	-	ePM1 70% (ISO 16890)-F7 (EN779)
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ambient air temperature max	°C	60
Ambient air temperature min	°C	-40

Ingress protection rating	-	IP22
Ingress protection rating of the drive	-	IP54

Dimensions