Breezy 160-E L07



Single-room HRV units with a copper heat exchanger, additional air quality sensors and control via a mobile app

- Power of electrical preheater: 100
- Sound pressure level LpA at 3 m: 42
- Heat exchanger material: Copper
- Filter: G3
- Control: Smartphone
- Casing material: Plastic
- Humidity sensor
- Temperature sensor
- Heater

	Unit of measurement	Breezy 160-E L07
Connected air duct size	mm	160
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	22
Power of electrical preheater	W	100
Unit current	A	0.62
Maximum airflow	m³/h	57
Sound pressure level LpA at 3 m	dB(A)	42
Heat recovery efficiency	%	88
Heat recovery efficiency, max	%	88
Heat exchanger material	-	Copper
Filter	-	G3
Transported air temperature (max)	°C	50
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IPX4
Minimum wall thickness	mm	560
Maximum wall thickness	mm	700

Dimensions

D	L	L1
162	800	700



Accessories

Other accessories

Name	Photo	Description
CPSO-40 Breezy 160		External compensator pad
CPSO-120 Breezy 160		External compensator pad
CPSO-160 Breezy 160		External compensator pad
CPSO-80 Breezy 160		External compensator pad
CPSO-200 Breezy 160		External compensator pad
MPS Breezy 160		Stainless steel cuff for external installation

SF Breezy G3		Filter (2 pcs.)
SF Breezy G4		Filter (2 pcs.)
SF Breezy G4 carbon		Filter (2 pcs.)