KSV 150 Duo Q G4/F8

Centrifugal inline fans with forward curved blades in sound-insulated casing with filters

- Sound pressure level LpA at 3 m: 25
- Filter: G4+F8
- Sound-insulated casing
- Impeller type: Centrifugal impeller with backward curved blades
- Casing material: Coated steel
- Installation in any position



	Unit of measurement	KSV 150 Duo Q G4/F8	
Speed	-	1	2
Connected air duct size	mm	150	
Phases	-	1	
Minimum supply voltage	V	230	
Maximum supply voltage	V	230	
Power supply frequency	Hz	50	
Rated power	W	41	50
Unit current	A	0.18	0.22
Maximum airflow	m^3/h	215	310
Rotation speed at 50hz	-	700	1200
Sound pressure level LpA at 3 m	dB(A)	15	25
Weight	kg	14.17	
Filter	-	G4+F8	
Transported air temperature (max)	°C	40	
Transported air temperature (min)	°C	-25	
Ingress protection rating	-	IPX4	
Ingress protection rating of the drive	-	IP44	
Impeller material	-	Plastic	



Dimensions

D	L	H	B	L1	B1	L2	B2
150	705	250	415	805	508	650	458



Ecodesign



Trademark	Vents					
Model	KSV 150 Duo Q G4/F8					
Specific energy consumption (SEC) (kWh/(m²/a))	Cold		Average		Warm	
	-50.7	A+	-23.6	C	-8.1	F
Type of ventilation unit	Unidirectional					
Type of drive installed	2-speed					
Type of heat recovery system	None					
Maximum flow rate (m³/h)	163					
Electric power input (W)	41					
Reference flow rate (m³/s)	0.049					
Reference pressure difference (Pa)	50					
Specific power input (SPI) (W/(m³/h))	0.252					
Control typology	Local demand control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	45					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	188		188		188	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	5536		2830		1280	