
OV 6D 450 (220V/60Hz)





Wall-mounted axial fans

- Impeller type: Axial
- Casing material: Coated steel
- Installation in any position

	Unit of measurement	OV 6D 450 (220V/60Hz)
Phases	-	3
Maximum supply voltage	V	400
Minimum supply voltage	V	400
Power supply frequency	Hz	60
Weight	kg	10.5
Transported air temperature (max)	°C	50
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IP24
Ingress protection rating of the drive	-	IP54
Impeller material	-	Coated steel



speed_1_60Hz
150
100
50
0
Static pressure [Pa]
0
2,000
4,000
Airflow [m3/h]


speed_1_60Hz
Static pressure [Pa]
100
50
0
0
2,000
Airflow [m3/h]



Dimensions

ØD	Ød	B	B1	L
465	11	576	535	230


ød
L
ØD
□B1
□B

Ecodesign

Trademark	Vents
Model	OV 6D 450 (220V/60Hz)
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal external pressure (Pa)	100
Maximum external leakage rates (%)	2.7
Static efficiency (%)	35
Effective electric power input (kW)	0.296
Declared typology	NRVU UVU
Sound power level (dB(A))	85