
OVK 6D 550





Wall-mounted axial fans

- Sound pressure level LpA at 3 m: 61
- Impeller type: Axial
- Casing material: Coated steel
- Installation in any position

	Unit of measurement	OVK 6D 550
Phases	-	3
Maximum supply voltage	V	400
Minimum supply voltage	V	400
Power supply frequency	Hz	50
Rated power	W	337
Unit current	A	0.9
Maximum airflow	m^3/h	6400
Sound pressure level LpA at 3 m	dB(A)	61
Weight	kg	16.5
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IP24
Ingress protection rating of the drive	-	IP54
Impeller material	-	Coated steel



speed_1
200
150
100
50
0
Static pressure [Pa]
0
5,000
10,000
Airflow [m3/h]


speed_1
100
75
50
25
0
Static pressure [Pa]
0
2,000
4,000
6,000
Airflow [m3/h]



Dimensions

ØD	ØD1	ØD2	Ød	L
570	645	710	11	260


L
ØD
Ød
ØD1
ØD2

Ecodesign

Trademark	Vents
Model	OVK 6D 550
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal external pressure (Pa)	140
Maximum external leakage rates (%)	2.7
Static efficiency (%)	38.7
Sound power level (dB(A))	93
Effective electric power input (kW)	0.656
Declared typology	NRVU UVU