Series **Boost-I EC**

Mixed-flow inline fans in sound-insulated casings with EC-motors

- Sound-insulated casing
- Impeller type: Mixed-flow
- Casing material: Galvanized steel



Lineup	Connected air duct size, mm	Phases	Rated power, W	Maximum airflow, m³/h	Temperature sensor	Number of speeds
 Boost-I 200 EC	200	1	121	1210	✕	1
 Boost-I 200 EC Un	200	1	121	1210	Remote	1
 Boost-I 200 EC R	200	1	121	1210	✕	1
 Boost-I 200 EC P	200	1	121	1210	✕	1
 Boost-I 250 EC	250	1	168	1750	✕	1
 Boost-I 250 EC Un	250	1	168	1750	Remote	1
 Boost-I 250 EC R	250	1	168	1750	✕	1

 Boost-I 250 EC P	250	1	168	1750	✕	1
 Boost-I 315 EC	315	1	353	3090	✕	1
 Boost-I 315 EC Un	315	1	353	3090	Remote	1
 Boost-I 315 EC R	315	1	353	3090	✕	1
 Boost-I 315 EC P	315	1	353	3090	✕	1
 Boost-I 355 EC	355	1	353	3500	✕	1
 Boost-I 355 EC Un	355	1	353	3500	Remote	1
 Boost-I 355 EC R	355	1	353	3500	✕	1
 Boost-I 355 EC P	355	1	353	3500	✕	1
 Boost-I 400 EC	400	1	726	5415	✕	1
 Boost-I 400 EC Un	400	1	726	5415	Remote	1
 Boost-I 400 EC R	400	1	726	5415	✕	1
 Boost-I 400 EC P	400	1	726	5415	✕	1