Series MPA



Supply units in the compact sound- and heat-insulated casing with water or electric heater

- Filter: G4
- Sound-insulated casing
- Casing material: Galvanized steel

Lineup	Connected air duct size, mm	Phases	Maximum supply voltage, V	Rated power, W	Maximum airflow, m³/h	Sound pressure level LpA at 3 m, dB(A)	Reheater
MPA 800 E1 LCD	400x200	1	230	245	800	35	Electric
MPA 1200 E3 LCD	400x200	3	400	410	1200	38	Electric
MPA 1800 E3 LCD	500x250	3	400	490	2000	40	Electric
MPA 2500 E3 LCD	500x300	3	400	650	2500	45	Electric
MPA 3200 E3 LCD	600x300	3	400	1270	3200	53	Electric
MPA 3500 E3 LCD	600x350	3	400	1270	3500	53	Electric

 MPA 800 W LCD	400x200	1	230	245	750	35	Water
 MPA 1200 W LCD	400x200	1	230	410	1200	38	Water
 MPA 1800 W LCD	500x250	1	230	490	1870	40	Water
 MPA 2500 W LCD	500x300	1	230	650	2150	45	Water
 MPA 3200 W LCD	600x300	3	400	1270	3000	53	Water
 MPA 3500 W LCD	600x350	3	400	1270	3250	53	Water
 MPA 5000 W LCD	800x500	3	400	1800	6500	55	Water