Series **Silenta-S**



Quiet axial extract fans with thin front panels

- Impeller type: Axial
- Casing material: Plastic
- Humidity sensor

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m³/h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Humidity sensor	Timer	Number of speeds
100 Silenta-S	100	7	78	26	✗	✗	✗	1
100 Silenta-S L	100	7	78	26	✗	✗	✗	1
100 Silenta-S K	100	7	78	26	✗	✗	✗	1
100 Silenta-ST	100	7	78	26	✗	✗	Turn off timer	1
100 Silenta-STH	100	7	78	26	✗	✓	Turn off timer	1
100 Silenta-SV	100	7	78	26	✓	✗	✗	1

 100 Silenta-SVT	100	7	78	26	✔	✘	Turn off timer	1
 100 Silenta-SVTH	100	7	78	26	✔	✔	Turn off timer	1
 125 Silenta-S	125	9.3	148	31	✘	✘	✘	1
 125 Silenta-S K	125	9.3	148	31	✘	✘	✘	1
 125 Silenta-S L	125	9.3	148	31	✘	✘	✘	1
 125 Silenta-ST	125	9.3	148	31	✘	✘	Turn off timer	1
 125 Silenta-STH	125	9.3	148	31	✘	✔	Turn off timer	1
 125 Silenta-SV	125	9.3	148	31	✔	✘	✘	1
 125 Silenta-SVT	125	9.3	148	31	✔	✘	Turn off timer	1
 125 Silenta-SVTH	125	9.3	148	31	✔	✔	Turn off timer	1
 150 Silenta-S	150	20	240	33	✘	✘	✘	1
 150 Silenta-S K	150	20	240	33	✘	✘	✘	1
 150 Silenta-S L	150	20	240	33	✘	✘	✘	1
 150 Silenta-ST	150	20	240	33	✘	✘	Turn off timer	1

 150 Silenta-STH	150	20	240	33	✗	✓	Turn off timer	1
 150 Silenta-SV	150	20	240	33	✓	✗	✗	1
 150 Silenta-SVT	150	20	240	33	✓	✗	Turn off timer	1
 150 Silenta-SVTH	150	20	240	33	✓	✓	Turn off timer	1
 150 Silenta-S (220 V/60 Hz)	150				✗	✗	✗	1
 150 Silenta-S K (220 V/60 Hz)	150				✗	✗	✗	1
 150 Silenta-S L (220 V/60 Hz)	150				✗	✗	✗	1
 150 Silenta-ST (220 V/60 Hz)	150				✗	✗	Turn off timer	1
 150 Silenta-STH (220 V/60 Hz)	150				✗	✓	Turn off timer	1
 150 Silenta-SV (220 V/60 Hz)	150				✓	✗	✗	1
 150 Silenta-SVT (220 V/60 Hz)	150				✓	✗	Turn off timer	1
 150 Silenta-SVTH (220 V/60 Hz)	150				✓	✓	Turn off timer	1