Series **Solid**



Axial decorative fans for extract ventilation

- Casing material: Plastic
- Humidity sensor

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m³/h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Humidity sensor	Timer	Number of speeds
100 Solid	100	8	85	27	✕	✕	✕	1
100 Solid Alu	100	8	85	27	✕	✕	✕	1
100 Solid Beige	100	8	85	27	✕	✕	✕	1
100 Solid Black Sapphire	100	8	85	27	✕	✕	✕	1
100 Solid Red	100	8	85	27	✕	✕	✕	1
100 Solid L	100	8	85	27	✕	✕	✕	1

 100 Solid L Black Sapphire	100	8	85	27	✗	✗	✗	1
 100 Solid L K	100	8	85	27	✗	✗	✗	1
 100 Solid T	100	8	85	27	✗	✗	Turn off timer	1
 100 Solid T Black Sapphire	100	8	85	27	✗	✗	Turn off timer	1
 100 Solid T L	100	8	85	27	✗	✗	Turn off timer	1
 100 Solid TH	100	8	85	27	✗	✓	Turn off timer	1
 100 Solid TH Black Sapphire	100	8	85	27	✗	✓	Turn off timer	1
 100 Solid Alu T	100	8	85	27	✗	✗	Turn off timer	1
 100 Solid Alu TH	100	8	85	27	✗	✓	Turn off timer	1
 100 Solid TH L	100	8	85	27	✗	✓	Turn off timer	1
 100 Solid TH L K	100	8	85	27	✗	✓	Turn off timer	1
 100 Solid V	100	8	85	27	✓	✗	✗	1
 100 Solid VTH	100	8	85	27	✓	✓	Turn off timer	1
 125 Solid	125	18	155	32	✗	✗	✗	1

 125 Solid Alu	125	18	155	32	✗	✗	✗	1
 125 Solid Black Sapphire	125	18	155	32	✗	✗	✗	1
 125 Solid Red	125	18	155	32	✗	✗	✗	1
 125 Solid T	125	18	155	32	✗	✗	Turn off timer	1
 125 Solid T Black Sapphire	125	18	155	32	✗	✗	Turn off timer	1
 125 Solid T1	125	18	155	32	✗	✗	Turn off timer	1
 125 Solid T L	125	18	155	32	✗	✗	Turn off timer	1
 125 Solid TH	125	18	155	32	✗	✓	Turn off timer	1
 125 Solid TH Black Sapphire	125	18	155	32	✗	✓	Turn off timer	1
 125 Solid TH L	125	18	155	32	✗	✓	Turn off timer	1
 100 Solid (120V/60Hz)	100				✗	✗	✗	1